CHEMWATCH 4612-49 CD 2014/6 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SX-50

SYNONYMS

neutralize salt corrosion add a protective coating

PRODUCT USE

Applied to any part of boat, trailer, Jet Ski, yacht, fishing tackle, outboard motor, 4x4, scuba gear or any surface exposed to salt, salt spray or sea water to neutralize salt corrosion and left to dry, it will leave a protective coating from further corrosion.

SUPPLIER

Company: Salt-X Australasia

Address: P.O. Box135 Rosewood QLD, 4340 Australia

Telephone: +61 419701082 email: neil@saltoff.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

May produce discomfort of the eyes*.

* (limited evidence)

SAFETY

Wear eye/face protection.

In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

CHEMWATCH 4612-49 CD 2014/6 Page 2 of 8

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME CAS RN % non hazardous ingredients, unregulated >60

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

Issue Date: Tues-17-June-2014

CHEMWATCH 4612-49 CD 2014/6 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES ...

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

FIRE INCOMPATIBILITY

None known.

HAZCHEM

None

Personal Protective Equipment

PERSONAL PROTECTION EQUIPMENT

Breathing apparatus. Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

None known

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Not available. Refer to individual constituents.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

HANDS/FEET

Wear chemical protective gloves, eg. PVC. Wear safety footwear or safety gumboots, eg. Rubber

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: Air Speed: solvent, vapours, degreasing etc., 0.25-0.5 m/s (50-100 f/min) evaporating from tank (in still air). aerosols, fumes from pouring 0.5-1 m/s (100-200 f/min.) operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow 1-2.5 m/s (200-500 f/min.) booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, 2.5-10 m/s (500-2000 f/min.) high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or
favourable to capture

2: Contaminants of low toxicity or of
nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in
motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the

CHEMWATCH 4612-49 CD 2014/6 Page 6 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear light blue liquid with no distinguishable odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Miscible
pH (1% solution): Not Available
Volatile Component (%vol): Not Available
Relative Vapour Density (air=1): Not Available
Lower Explosive Limit (%): Not Applicable
Autoignition Temp (°C): Not Applicable

State: Liquid

Boiling Range (°C): 111

Specific Gravity (water=1): 1.09 pH (as supplied): Not Available Vapour Pressure (kPa): Not Available Evaporation Rate: <1 BuAC = 1 Flash Point (°C): Not Applicable

Upper Explosive Limit (%): Not Applicable Decomposition Temp (°C): Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of

Section 11 - TOXICOLOGICAL INFORMATION ...

the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

SX-50

Not available. Refer to individual constituents. unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

Section 12 - ECOLOGICAL INFORMATION

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

CHEMWATCH 4612-49 CD 2014/6 Page 8 of 8

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:

None

Dangerous Goods Class: None

UN/NA Number: None ADR Number: None Packing Group: None Labels Required: None

Additional Shipping Information: None International Transport Regulations: None

IMO: None

HAZCHEM

None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Tues 17-June-2014 Print Date: Tues 17-June-2014